



Southern Pipe, Inc.

P. O. Box 606, 135 Random Drive, New London, NC 28127
 Phone: 704-463-5202 Fax: 704-463-5203 www.southern-pipe.com

**SCHEDULE 40 CONDUIT
 HEAVY WALL RIGID PVC NONMETALLIC CONDUIT
 FOR USE IN ABOVE GROUND AND UNDERGROUND APPLICATIONS**

SIZE	PART NUMBER	DESCRIPTION	MIN WALL	O.D.	WEIGHT PER 100'	PALLET QTY
1/2"	41505 42505	10 FT BE 20 FT BE	.109	.840	16	6000 12000
3/4"	41508 42508	10 FT BE 20 FT BE	.113	1.050	22	4400 8800
1"	41510 42510	10 FT BE 20 FT BE	.133	1.315	32	3600 7200
1 1/4"	41512 42512	10 FT BE 20 FT BE	.140	1.660	43	3300 6600
1 1/2"	41515 42515	10 FT BE 20 FT BE	.145	1.900	52	2250 4500
2"	41520 42520	10 FT BE 20 FT BE	.154	2.375	70	1400 2800
2 1/2"	41525 42525	10 FT BE 20 FT BE	.203	2.875	125	930 1860
3"	41530 42530	10 FT BE 20 FT BE	.216	3.500	156	880 1760
3 1/2"	41535 42535	10 FT BE 20 FT BE	.226	4.000	188	630 1260
4"	41540 42540	10 FT BE 20 FT BE	.237	4.500	223	570 1140
5"	41550 42550	10 FT BE 20 FT BE	.258	5.563	310	380 760
6"	41560 42560	10 FT BE 20 FT BE	.280	6.625	395	260 520
*8"	41580	10 FT BE	.322	8.625	547	140

Southern Pipe Schedule 40 Conduit is produced to the following Standards:

Underwriters Laboratory, Inc.® (UL)	UL 651
National Electrical Manufacturers Association (NEMA)	TC-2
National Electrical Manufacturers Association (NEMA)	TC-18
Federal Specification	WC-1094-A

* 8" Sch 40 is a non (UL) LISTED product

Rated for 90° C



RUS listed
 Sunlight Resistant